



Model OBBL Series

밴딩빔형 로드셀 (20kg ~ 200kg)

밴딩빔형 고정밀도 로드셀입니다.


- 고강도 알루미늄 사용
- 고정밀 & 저가격



사 양

모 델	OBBL
정격용량 (R.C.)	20, 50, 100, 200kg
정격출력 (R.O.)	2mV/V ± 0.25%
비직선성	≤ 0.03% R.O.
히스테리시스	≤ 0.02% R.O.
반복성	≤ 0.02% R.O.
크리이프	≤ 0.03% in 20min.
제로발란스	≤ 1% R.O.
온도보상범위	-10 ~ 70°C
허용온도범위	-20 ~ 80°C
출력의 온도영향	≤ 0.03% LOAD/10°C
영점의 온도영향	≤ 0.03% R.O./10°C
입력간저항	430 Ohms ± 20 Ohms
출력간저항	350 Ohms ± 5 Ohms
절연저항	2000 MOhms at 50V DC
인가전압	10V(Recommended), 15V(Maximum)
연결케이블	Ø5mmx3m(22AWG x 4Core Shielded)
보호등급	meets IP 65
허용과부하	150% R.C
극한과부하	300% R.C

형식명	OBBL - 50
모델	용량
OBBL	20, 50, 100, 200kg



Installation

